

# Rig Wash

Degreaser

- *Free Rinsing*
- *Non-Flammable*
- *No VOC's*

## Description

---

RIGWASH cleaner/ degreaser contains a complex and unique mixture of nonionic and anionic plant-based surfactants with natural mineral complexing agents. RIGWASH is an excellent choice for chemical cleaning of hydrocarbon foulants such as oils, greases, waxes, gums, tars and coke. Safe on all ferrous and non-ferrous metals. RIGWASH degreaser provides a highly effective and easy-to-use alternative to compounds containing volatile organic solvents, halogenated solvents, petroleum-based degreasers and inorganic phosphates. Contains no heavy metals - biodegradable and exhibits little environmental impact when disposed of properly. On-site use eliminates cost of dismantling equipment, sending it off-site for cleaning services and reassembling.

## Packaging/ Handling

---

RIGWASH is available in 4L jugs, 20L pails, 210L drums, 1000L totes and in bulk. Before using this product please refer to the Material Safety Data Sheet for all safety and handling information. Please contact your local area manager for various application details.

This green product works superior to conventional non-green products and is Environmentally Safe.

## Application

---

Rig Wash is designed to clean, long haul rigs, oilrigs, car wash facilities. Rig Wash is ideal for cleaning on and off-shore drilling rigs and equipment. Use it for continued maintenance of platforms, decks, derricks, racks, liners, casing, drills, bits and rods. It's ideal for PC pumps, ESP pumps, pump jacks, pump pads, crown & traveling blocks, blowout preventers and more. RIGWASH can be diluted: 1 part concentrate with 10-20 parts water for general light cleaning. For heavy duty cleaning dilute 1 part RIGWASH with 5-10 parts water depending on soil. Note: Soil conditions will vary, therefore trial of different dilution rates is recommended to determine proper dilution for the job. Directions - Apply by pressure wash, brush, mop or spray. Dilution rates depend on the type of contamination and the degree of soiling, the type of crude and its location as well as the type of oil/pseudo-based mud systems used. Can be diluted with fresh or seawater. We recommend for heavy duty cleaning: 1 to 5, general cleaning: 1 to 10, light degreasing: 1 to 40-80.

## Physical Properties

---

Physical State:	Liquid
Odour/Appearance:	Water thin, clear blue, mild odor
Specific Gravity:	1.04 +/-0.05
Solubility in water:	Soluble
Freezing Point:	0 °C/ 32 °F
Boiling Point:	100 °C/ 212 °F
pH:	11.5 +/- 0.2

NITMOI LABS INC.  
29 Centennial Road  
Units 6-7  
Orangeville, ON  
Canada L9W 1R1  
519.217.6172  
nitmoilabs.com



**NITMOI LABS INC.**  
Solutions for a **sustainable** future  
Solutions pour un avenir **durable**